Evidence of Performance

Air permeability, Watertightness, Resistance to wind load, Operating forces

Test Report No. 11-001615-PR01 (PB-A01-0203-en-01) ROSENHEIM

Client ELVIAL S.A.

Aluminium Extrusion 26th km national road 61100 Santa-Kilkis

Greece

Product Lifting sliding casement door

Designation System designation: Lift and slide EL6700

Performance-relevant

product details

Overall dimensions

(WxH)

Special features

Material: Aluminium profiles with thermal break

3,000 mm x 2,200 mm

Sealing additional sealed with pourable sealant

Results

Air permeability according to EN 12207:1999-11



Class 4

Watertightness according to EN 12208:1999-11



Class 4A

Resistance to wind load

according to EN 12210:1999-11/AC:2002-08



Class C2 / B2

Operating forces according to EN 13115:2001-07



Class 0

ift Rosenheim

28. October 2011

Robert Kolacny, Dipl.-Ing. (FH)
Deputy Head of Testing Department
Building Components

Peter Marquardt, Dipl.-Ing. (FH)
Operating Testing Officer
Tightness & Wind Load

Basis

EN 14351-1:2006+A1:2010

Test standard/s: EN 1026:2000-06 EN 1027:2000-06 EN 12046-1:2000-02 EN 12211:2000-06 Correspond/s to the national standard/s (e.g. DIN EN)

Representation



Instructions for use

The results obtained can be used by the manufacturer as the basis for the manufacturer ITT test report summary. Observe the specifications set out by the applicable product standard.

Validity

The data and results refer solely to the tested and described specimen. Classification remains valid as long as the product and the above basis remain unchanged. The results can be extrapolated under the manufacturer's own liability subject to observance of the relevant specifications set out by the applicable product standard. This test/evaluation does not allow any statement to be made on any further characteristics regarding performance and quality of the construction presented, in particular the effects of weathering and ageing were not taken into account.

Notes on publication

The **ift**-Guidance Sheet "Advertising with ift test documents" applies. The cover sheet can be used as an abstract.

The report contains a total of 28 pages.



ift Rosenheim GmbH

Geschäftsführer: Dipl.-lng. (FH) Ulrich Sieberath Dr. Jochen Peichl Theodor-Gietl-Str. 7 - 9 D-83026 Rosenheim Tel.: +49 (0)8031/261-0 Fax: +49 (0)8031/261-290 www.ift-rosenheim.de Sitz: 83026 Rosenheim AG Traunstein, HRB 14763 Sparkasse Rosenheim Kto. 3822 BLZ 711 500 00 Notified Body Nr.: 0757 Anerkannte PÜZ-Stelle: BAY 18

Deutscher Akkreditierungs DAP-PL-0808 99 DAP-ZE-2288 00